

Item No. _____

Quantity _____



Job Name _____

Spec No. _____



CSR-9M

CSR-4M



Inclined can guides provide easy access and facilitate stock rotation when loaded from rear.

CAN RACKS

ALL-WELDED FULL & HALF SIZE
ALUMINUM CONSTRUCTION

Custom Sizes Available

Model	Description	H	W	D	Weight
FULL-SIZE, CAPACITY: 162 – #10 CANS					
CSR-9	Stationary	76"	25½"	35"	53
CSR-9M	Mobile	82"	25½"	35"	73
HALF-SIZE, CAPACITY: 72 – #10 CANS					
CSR-4M	Aluminum Top	43"	25¾"	35¼"	43
CSR-4MP	Poly Top	43"	25¾"	35¼"	57
CSR-4MS	Stainless Top	43"	25¾"	35¼"	48
HALF-SIZE, CAPACITY: 54 – #10 CANS					
CSR-3	No Top	34"	25¾"	35¼"	30
CSR-3M	Aluminum Top	34"	25¾"	35¼"	39
CSR-3MP	Poly Top	34"	25¾"	35¼"	53
CSR-3MS	Stainless Top	34"	25¾"	35¼"	44

Options:

/011 Caster Brakes (2)

APPLICATIONS: Can holding, storing and organization. Inclined angle and T-Bar guides provides easy access for can selection, rotation and inventory control. Holds both #10 and or #5 cans. Front or rear loading. First in first out when loaded from rear.

CONSTRUCTION: Heavy duty, high tensile extruded aluminum. Type 6063-T5 alloy. Lifetime guarantee against rust and corrosion. Shipped assembled for immediate use.

CAN SLIDES: Sides are 1" x 1-1/2" extruded aluminum angle and T-bar heli-arc welded to frame. Bottom load ledge design.

FRAME AND CROSS SUPPORTS: Vertical and horizontal frame sections are 1-1/4" extruded aluminum tubing.

CASTERS: Standard 5" full swivel non-marking casters. Casters are securely bolted to frame to facilitate replacements.



Notes

55 Channel Drive • Port Washington, NY 11050-2216
 8891 NW 102nd Street • Medley, FL 33178
 Tel: 516-944-6271 • Fax: 516-944-0625
 Toll Free: 866-712-7283
 www.channelmfg.com • Email: sales@channelmfg.com