

Amana® Commercial

Project #: _____

Item #: _____



Model RCS10DS shown

Medium Volume

This category of microwave is ideal for...

Applications:

- Coffee shops
- Ethnic restaurants
- Concessions
- Dessert stations



All ACP, Inc. commercial ovens are backed by our Culinary Center. Call us with any question regarding food preparation, menu development and cooking times. 866-426-2621.

Medium Volume

Amana Commercial Microwave Model RCS10DS

Power Output

- 1000 watts of power.
- Full power only for simple operation.

Easy to Use

- User friendly six minute dial timer lights up for at-a-glance monitoring.
- Timer must be manually reset to zero if door is opened during heating.
- See-through door and lighted interior for monitoring without opening the door.
- 1.2 cubic ft. (.034m³) capacity accommodates a 14" (356 mm) platter, prepackaged foods and single servings.
- Stackable to save valuable counter space.

Easy to Maintain

- Stainless steel exterior and interior for easy cleaning and a commercial look.
- Constructed to withstand the foodservice environment.
- Non-removable air filter protects oven components.
- Limited 3 year warranty.
- Backed by the ACP, Inc. 24/7 ComServ Support Center, 866-426-2621.
- UL and ETL Listed.




A/A File #:

Specification #:



Amana Commercial Microwave Model RCS10DS | Medium Volume




Installation clearance: 2" all sides

Drawings available from KCL CADlog - techs@kclcad.com

Specification #:

Specifications

Model	RCS10DS	UPC Code	728028020731
Configuration	Countertop		
Control System	Dial		
Max. Cooking Time	6:00		
Power Levels	1		
Time Entry Option	Yes		
Microwave Distribution	Rotating antenna, top		
Magnetron	1		
Stackable	Yes		
Stage Cooking	1		
Interior Light	Yes		
Door Handle	Grab & Go		
Signal	End of cycle		
Exterior Dimensions	H 13 3/4" (349.25)	W 22" (558.8)	D*19" (482.6)
Cavity Dimensions	H 8 1/2" (216)	W 14 1/2" (368.3)	D 15" (381)
Door Depth	34 3/4" (882.65), 90°+ door open		
Usable Cavity Space	1.2 cubic ft. (.034 m ³)		
Exterior Finish	Stainless steel		
Interior Finish	Stainless steel		
Power Consumption	1550 W, 13 A		
Power Output**	1000 W** Microwave		
Power Source	120V, 60 Hz, 15 A single phase		
Plug Configuration / Cord	NEMA 5-15	5 ft. (1.5m)	
Frequency	2450 MHz		
Product Weight	41 lbs. (18.6 kg.)		
Ship weight (approx.)	48 lbs. (21.8 Kg.)		
Shipping Carton Size	H 17 1/4" (431)	W 25 1/2" (660)	D 20 1/2" (508)
UPS Shippable	Yes		

Measurements in () are millimeters

* Includes handle

** IEC 705 Tested

AIA File #:

Specifications

Commercial microwave shall have a user-friendly 6 minute dial timer with illuminated digits and an end of cycle audible signal. Timer shall not automatically reset if the door is opened during heating. There shall be a single power level and cooking stage. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 90°+ opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (.034 m³) cavity shall accommodate a 14" (356 mm) platter. Interior ceramic shelf shall be sealed and recessed on oven bottom to reduce plate-to-shelf edge impact. Oven shall have a stainless steel exterior and interior and be stackable to save counter and shelf space. The air filter shall be permanently affixed to the front of the oven. Microwave oven shall comply with standards set by the U.S Department of Health and Human Services, UL for safety and ETL for sanitation.



Warranty

Limited 3 year warranty:

Year 1 - parts, labor, and travel are covered.

Years 2 - 3 - magnetron tube (part only) is covered.

Service

All products are backed by the ACP, Inc. 24/7 ComServ Support Center.

