



LUXURA SUSHI - Counter Top Refrigerated Display Case

Colors Available: **Black & Silver**

Our DC Series features ultra-modern and sophisticated design; incorporating curved front tempered glass, with eye-catching appeal and attractive product visibility.



***No Drain Connection Required**

Photo represents: DC-6BK-L

- ✓ Designed to display sushi, meats, salads, desserts and many other items for quick point of purchase sales
- ✓ Curved front tempered glass for added visibility, safety and increased durability
- ✓ New enlarged front hinged glass tilts forward to simplify cleaning and maximize eye appeal
- ✓ Interior lighting (with protective cover) enhances overall product appearance
- ✓ Removable sliding rear doors allow for easy access and simplify cleaning
- ✓ Special "cold-diffusion" system provides uniformity of temperature throughout
- ✓ Upper double evaporator fin-type coil assures proper temperature throughout the cabinet, eliminating any danger of bacteria or food contamination
- ✓ SMARTEMP electronic thermostat maintains temperatures between 33°F/1°C and 40°F/7°C, digitally displays temperature at all times, and reaches the required temperature in only a few minutes
- ✓ Upper stainless steel baffle plate creates a drip-free food safe environment
- ✓ In addition to the on/off switch, an added safety feature is incorporated whereby an automatic cut-off system will switch on/off the motor whenever defrosting is necessary
- ✓ Available in Black or silver with either a left side or right side compressor
 - " For "L" models, compressor is at the left side when facing controls
 - " For "R" models, compressor is at the right side when facing controls



- Photo represents: DC-6S-L
- Front glass opening for easy cleaning!





FEATURES

- Silent and sealed compressor with a double-vented high quality condensor
- 304 finish stainless steel deep drawn inner body
- Available in either a silver or black exterior finish
- Condensate from upper coil drains directly into a self contained evaporation channel, eliminating any drain connection requirement
- "Foamed-in-place" injected polyurethane lateral profiles
- Environmentally-friendly R-134A type freon and injected insulation throughout the entire body
- Designed to operate in an air-conditioned environment under a maximum ambient temperature of 77°F/25°C with a relative humidity of 55%

CONSULTANT SPECIFICATION

The display case shall be a Kool-It "DC" series unit equipped with; a SMARTEMP electronic thermostat with digital temperature indicator, internal encased cool fluorescent light, a hinged/tilting curved tempered front glass, an upper double evaporator fin-type coil, an automatic drainage and evaporation system, removable rear sliding access doors, and a two year warranty on the condensor & compressor. It must be rated at 115V, be equipped with a 0.25 h.p. compressor, and come available in an anodized aluminum silver or black finish.

| MODEL | COLOR | WIDTH | | DEPTH | | HEIGHT | | NET | | MAX | | SHIPPING SPECS | | | |
|---------------|--------|-------|-------|-------|-------|--------|------|----------|--------------|-------|-------|----------------|---------|--|--|
| | | EXT. | INT. | EXT. | INT. | EXT. | INT. | WEIGHT | CAPACITY | WIDTH | DEPTH | HEIGHT | WEIGHT | | |
| DC-4BK-L or R | BLACK | 47" | 31.5" | 15.6" | 11.8" | *12.3" | 6.2" | 76 lbs. | 1.42 cu. ft. | 55.4" | 23.2" | 22.5" | 140 lbs | | |
| DC-5S-L or R | SILVER | 57" | 41.3" | 15.6" | 11.8" | *12.3" | 6.2" | 88 lbs. | 1.74 cu. ft. | 66.2" | 23.2" | 22.5" | 165 lbs | | |
| DC-5BK-L or R | BLACK | | | | | | | | | | | | | | |
| DC-6S-L or R | SILVER | 70.5" | 55" | 15.6" | 11.8" | *12.3" | 6.2" | 99 lbs. | 2.32 cu. ft. | 79.2" | 23.2" | 22.5" | 191 lbs | | |
| DC-6BK-L or R | BLACK | | | | | | | | | | | | | | |
| DC-7S-L or R | SILVER | 84.3" | 70" | 15.6" | 11.8" | *12.3" | 6.2" | 112 lbs. | 2.95 cu. ft. | 91.3" | 23.2" | 22.5" | 220 lbs | | |
| DC-7BK-L or R | BLACK | | | | | | | | | | | | | | |

- “ For “L” models, compressor is at the left side when facing controls
- “ For “R” models, compressor is at the right side when facing controls
- * Units come equipped with 1” legs and optional 4” legs.

SPECIFICATIONS

- Electrical: 115/60/1
- Voltage Variation: + - 10%
- Rated Amperage: 4.5 A
- Maximum Ambient Temperature: 77°F/25°C
- Saturation Temperature: 33°F/1°C
- (Ambient Temp. 77°F/25°C, No Load)
- Refrigerant Type: R-134A
- Maximum Load Height: 6.2"



IMPORTANT: This unit does not have an automatic defrost system and must be turned off at night to allow the evaporators to defrost.

WARRANTY: One (1) year parts & labor, two (2) years on the condensor & compressor

MVP GROUP CORPORATION

5659 Royalmount Ave. Montreal, QC Canada H4P 2P9
Tel: 514-737-9701 888-275-4538 Fax: 514-342-3854
www.mvpgroupcorp.com / sales@mvpgroupcorp.com

