



Item No. _____
 Project _____
 Quantity _____

Electric, Cheesemelter

Model: MM[24,36,48]-[C,P,W]



Model MM24-W shown

SIZING AND PERFORMANCE GUIDE

Model	Width	KW Input
MM24	24"	2.4
MM36	36"	3.6
MM48	48"	4.8

SHORT/BID SPECIFICATION

Cheesemelter shall be a **LANG Manufacturing Model MM__** [specify width: 24, 36 or 48 inches]-__ [specify style: -C Counter, -P Pass-Through or -W Wall Mount] unit with 1200 Watts per foot of electric infrared quartz heaters; Weight-of-Plate instant ON/OFF and constant heat setting; large, unrestricted plate opening; four position adjustable plate rack; and all the features listed and the options/accessories checked:

STANDARD PRODUCT WARRANTY

- One year, parts & labor
- 90 day warranty on quartz heaters
 [Heater Guards available. See OPTIONS]

CONSTRUCTION FEATURES

- Stainless steel front, top & sides, with aluminized steel back
- Top mounted, direct wired quarts infrared heaters
- Four position, adjustable chrome plated plate rack
- 4" adjustable legs provided with [-C] Counter & [-P] Pass-Through models
- Wall mounting brackets included with Wall-Mount [-W] Models

PERFORMANCE FEATURES

- Weight-of-Plate instant-on/off saves time and energy
- Weight-of-Plate instant-on eliminates pre-heating
- Efficient quartz heating elements deliver 1650°F heat
- Large, unrestricted opening for quick and easy plate access
- Dual controls allows half use of 48" model, to save energy

CONTROL PACKAGE

- Weight-of-Plate automatic heat ON-OFF
- Power ON switch
- Automatic [plate activated]/Constant-Heat Switch
- HEATING indicator light
- MM48 [48"] Model has dual controls for left side only heating or both sides




Sheet No. **LSP-CM2** (rev. 9/03)

INSTALLATION REQUIREMENTS

- (E) [MM24 & MM36]: 208V or 240V, 1-phase; [MM48] 208V or 240V, 1-Phase or 3-Phase electrical connection
- Heat shield required when mounting over heat source & shipped with [-W] Wall-Mounted Models
- Unit not to be installed over charbroiler [Connection from rear. See below for location and delivery requirements]

OPTIONS & ACCESSORIES

- Extra chrome plated racks [specify size: 24" etc.]
- 2' wire heater guard [Two required for MM48 Model]
- 3' wire heater guard
- Stainless steel protective bottom. For wall mounting above other equipment [Specify Model: MM36 etc.]
- Stainless Steel Wall-Mount Kit. To convert Pass-Through to Counter or Wall Mount unit [Specify Model: MM36 etc.]



Model	Height x Width x Depth (Not including legs)	Clearance from combustible surface	Weight		Freight Class
			Actual	Shipping	
MM24	19.5" x 24.0" x 16.8"	Sides: 2" Back: 0" Bottom: 4"	90 lbs.	105 lbs.	85
	496mm x 610mm x 426mm		41 kg	48 kg	
MM36	19.5" x 36.0" x 16.8"	Pass-Through Models: Front & Back: 15"	110 lbs.	130 lbs.	85
	496mm x 915mm x 426mm		50 kg	59 kg	
MM48	19.5" x 48.0" x 16.8"		145 lbs.	180 lbs.	85
	496mm x 1220mm x 426mm		66 kg	82 kg	

Voltage	(E) Electrical Requirements By Model						
	Phase	Model MM24		Model MM36		Model MM48	
		Total kW	Amps/Line	Total kW	Amps/Line	Total kW	Amps/Line
208V/60Hz	1	2.4	11.5	3.6	17.3	4.8	23.1
240V/60Hz	1	2.4	10.0	3.6	15.0	4.8	20.0
208V/60Hz	3	n/a	n/a	n/a	n/a	4.8	20.0
240V/60Hz	3	n/a	n/a	n/a	n/a	4.8	17.3

CAD SYMBOLS & PRICING



Due to continuous improvements, specifications subject to change without notice.



Sheet No. LSP-CM2 (rev. 9/03)

LANG MANUFACTURING COMPANY • 6500 Merrill Creek Parkway, Everett, WA 98203
TOLL FREE: 800.882.6368 • FAX: 425.349.2733 • www.langworld.com