

# Display Cases - Deli



## Double Duty Deli Cases

Model	Doors	Cu. Ft.	Stainless Shelves	HP	Amps	Crated Weight	Cabinet Dimensions		
							L	D†	H
TDBD-72-2	2	35	1 full length	1/2	14.0	640	72 1/8	35 1/8	55
TDBD-72-4	4	35	1 full length	1/2	14.0	625	72 1/8	35 1/8	55
TDBD-96-3	3	46	2 half length	3/4	16.0	850	96 1/8	35 1/8	55
TDBD-96-6	6	46	2 half length	3/4	16.0	900	96 1/8	35 1/8	55

All dimensions rounded up to the nearest 1/8"

† Depth does not include 1/2" for threaded drain fitting.



TDBD-72-2



TDBD-96-6



### FEATURES/BENEFITS

- Oversized, **environmentally friendly (134A) gravity coil refrigeration system.**
- Refrigerator **holds ideal 38°F to 40°F** case temperature for fresher deli products.
- True double duty deli cases are classified by UL to the NSF standard 7.
- **Stainless steel exterior** (white laminated vinyl rear louvered grill).
- Interior - attractive, **NSF approved**, white aluminum sides and top, **300 series stainless steel floor with coved corners.**
- **Refrigerated lower rear storage.**
- **115V receptacle for scales or slicers.**
- Exclusive front and rear interior lighting.
- **Fluorescent lamps are low UV emitting** - red meats are enhanced in faithful color.
- Adjustable upper stainless steel shelf. One level of shelving standard. (extra stainless steel shelf is optional for TDBD-72's only)
- Each deli is designed with **energy efficient, "Low-E", thermal** product viewing glass to maximize your cold product presentations.
- Foamed-in-place **high density polyurethane insulation (CFC free).**
- Positive seal, energy saving, self-closing doors.
- Automatic defrost time clock.
- Space saving design.
- Self-contained system.
- Available with optional legs or 2 1/2" or 4" diameter castors.

Remote cabinets available 14% off list (condensing units supplied by others). Consult factory technical service dept. for BTU information.