



## Underbar Refrigeration

### Direct Draw Beer Dispensers



TDD-1

Model	1/2 Barrels	Doors	HP	Amps	Crated Weight	Cabinet Dimensions		
						L	D	H*
TDD-1	1	1	1/5	4.4	180	23 <sup>1</sup> / <sub>2</sub>	31 <sup>1</sup> / <sub>4</sub>	39 <sup>3</sup> / <sub>4</sub>
TDD-2	2	2	1/3	8.5	305	58 <sup>7</sup> / <sub>8</sub>	27 <sup>1</sup> / <sub>8</sub>	37
TDD-3	3	2	1/3	8.5	335	69 <sup>1</sup> / <sub>8</sub>	27 <sup>1</sup> / <sub>8</sub>	37
TDD-4	4	3	1/3	8.5	415	90 <sup>3</sup> / <sub>8</sub>	27 <sup>1</sup> / <sub>8</sub>	37

All dimensions rounded up to the nearest 1/8"

\* Height does not include 15<sup>1</sup>/<sub>4</sub>" for draft arm.

### Stainless Steel Direct Draw Beer Dispensers

Model	1/2 Barrels	Doors	HP	Amps	Crated Weight	Cabinet Dimensions		
						L	D	H*
TDD-1-S	1	1	1/5	4.4	175	23 <sup>1</sup> / <sub>2</sub>	31 <sup>1</sup> / <sub>4</sub>	39 <sup>3</sup> / <sub>4</sub>
TDD-2-S	2	2	1/3	8.5	305	58 <sup>7</sup> / <sub>8</sub>	27 <sup>1</sup> / <sub>8</sub>	37
TDD-3-S	3	2	1/3	8.5	340	69 <sup>1</sup> / <sub>8</sub>	27 <sup>1</sup> / <sub>8</sub>	37
TDD-4-S	4	3	1/3	8.5	415	90 <sup>3</sup> / <sub>8</sub>	27 <sup>1</sup> / <sub>8</sub>	37

All dimensions rounded up to the nearest 1/8"

\* Height does not include 15<sup>1</sup>/<sub>4</sub>" for draft arm.



TDD-3



TDD-4-S

### FEATURES/BENEFITS

- Oversized **environmentally friendly (134A) forced-air refrigeration system** for maximum performance.
- Provides ice cold products **33°F to 38°F** (normal ambient conditions).
- Attractive, wear-resistant laminated heavy duty black vinyl exterior.
- Heavy gauge **all stainless steel countertop**.
- Interior - **300 series stainless steel floor** with 1/2" lip & heavy galvanized steel walls.
- Interior - NSF approved for pre-packaged and bottled goods.
- **3" diameter stainless steel insulated beer columns.**
- Fan motors direct large volume of cold air into draft columns.
- **Door locks - standard.**
- Recessed handles.
- Each cabinet designed to accommodate all types of beer kegs.
- **Incandescent interior lighting** (excluding TDD-1).
- Air vents on side to maximize flow of fresh air through condenser.
- Simple plug-in installation.
- Available with optional legs or 2<sup>1</sup>/<sub>2</sub>" or 4" diameter castors (Castors standard equipment on TDD-1, legs not available).

#### Stainless Steel Models

- Stainless steel exterior and countertop for those who appreciate the value of stainless.
- Castors standard equipment on TDD-1-S (legs not available).

Remote cabinets available 14% off list  
 Unavailable for TDD-1 & TDD-1-S.  
 (condensing units supplied by others).  
 Consult factory technical service dept. for BTU information.