



Milk Coolers

Milk Coolers

Forced air refrigeration system designed to create colder temperatures for improved milk safety.



TMC-34



TMC-49-S

Dual access Milk Cooler provides convenient stocking and servicing.



TMC-58-DS

Model	Doors	Cu. Ft.	Crate Capacity	Floor Racks	HP	Amps	Crated Weight	Cabinet Dimensions L** D† H*		
<i>(white aluminum interior/white vinyl & stainless steel exterior)</i>										
TMC-34	2	13.8	8	2	1/3	8.3	325	34 x 33 ³ / ₈ x 41 ¹ / ₂		
TMC-49	2	20.9	12	3	1/3	8.2	410	49 x 33 ³ / ₈ x 41 ¹ / ₂		
TMC-58	2	24.5	16	3	1/3	9.1	445	58 x 33 ³ / ₈ x 41 ¹ / ₂		
<i>(white aluminum interior/stainless steel exterior)</i>										
TMC-34-S	2	13.8	8	2	1/3	8.3	310	34 x 33 ³ / ₈ x 41 ¹ / ₂		
TMC-49-S	2	20.9	12	3	1/3	8.2	410	49 x 33 ³ / ₈ x 41 ¹ / ₂		
TMC-58-S	2	24.5	16	3	1/3	9.1	445	58 x 33 ³ / ₈ x 41 ¹ / ₂		
<i>(stainless steel interior/white vinyl & stainless steel exterior)</i>										
TMC-34-SS	2	13.8	8	2	1/3	8.3	310	34 x 33 ³ / ₈ x 41 ¹ / ₂		
TMC-49-SS	2	20.9	12	3	1/3	8.2	410	49 x 33 ³ / ₈ x 41 ¹ / ₂		
TMC-58-SS	2	24.5	16	3	1/3	9.1	445	58 x 33 ³ / ₈ x 41 ¹ / ₂		
<i>(stainless steel interior/stainless steel exterior)</i>										
TMC-34-S-SS	2	13.8	8	2	1/3	8.3	330	34 x 33 ³ / ₈ x 41 ¹ / ₂		
TMC-49-S-SS	2	20.9	12	3	1/3	8.2	415	49 x 33 ³ / ₈ x 41 ¹ / ₂		
TMC-58-S-SS	2	24.5	16	3	1/3	9.1	445	58 x 33 ³ / ₈ x 41 ¹ / ₂		

All dimensions rounded up to the nearest 1/8".

* Height does not include 5 1/8" for castors.

† Depth does not include 1" each side for bumpers.

** Length does not include 1/8" each side for lid pins.

Dual Sided Milk Coolers

Model	Doors	Cu. Ft.	Crate Capacity	Floor Racks	HP	Amps	Crated Weight	Cabinet Dimensions L** D† H*		
<i>(white aluminum interior/white vinyl & stainless steel exterior)</i>										
TMC-49-DS	4	20.9	12	3	1/2	9.3	445	49 x 33 ³ / ₈ x 41 ¹ / ₈		
TMC-58-DS	4	24.5	16	3	1/2	10.4	495	58 x 33 ³ / ₈ x 41 ¹ / ₈		
<i>(white aluminum interior/stainless steel exterior)</i>										
TMC-49-S-DS	4	20.9	12	3	1/2	9.3	435	49 x 33 ³ / ₈ x 41 ¹ / ₈		
TMC-58-S-DS	4	24.5	16	3	1/2	10.4	485	58 x 33 ³ / ₈ x 41 ¹ / ₈		
<i>(stainless steel interior/white vinyl & stainless steel exterior)</i>										
TMC-49-DS-SS	4	20.9	12	3	1/2	9.3	435	49 x 33 ³ / ₈ x 41 ¹ / ₈		
TMC-58-DS-SS	4	24.5	16	3	1/2	10.4	485	58 x 33 ³ / ₈ x 41 ¹ / ₈		
<i>(stainless steel interior/stainless steel exterior)</i>										
TMC-49-S-DS-SS	4	20.9	12	3	1/2	9.3	435	49 x 33 ³ / ₈ x 41 ¹ / ₈		
TMC-58-S-DS-SS	4	24.5	16	3	1/2	10.4	485	58 x 33 ³ / ₈ x 41 ¹ / ₈		

All dimensions rounded up to the nearest 1/8".

* Height does not include 5 1/8" for castors.

† Depth does not include 1" each side for bumpers.

** Length does not include 1/8" each side for lid pins.

FEATURES/BENEFITS

- Environmentally friendly (134A) **forced-air** refrigeration.
- **Holds milk 33°F to 38°F.**
- Stainless steel or combination stainless/white vinyl exterior.
- Exterior custom colors/graphics available as an upcharge (consult factory).
- **Reinforced, 300 series stainless steel interior floor.**
- Interior - attractive, **NSF approved**, white aluminum or 300 series stainless steel.
- Digital thermometer standard for easy visibility.
- **Easy-roll, all swivel 4" diameter castors** (front castors lock in place).
- Locks standard.
- **Heavy duty floor rack standard.**
- Convenient clean out drain standard.
- Door support bumpers.
- Dual sided models offer convenient, efficient access to refrigerated product.
- "Hold open" flip-up top feature, standard.
- Self-service doors feature convenient drop front and flip-up top.
- Self-contained system.
- Available with optional corner bumpers.
- A variety of exterior color options available (see www.truemfg.com for the latest offerings).
- See www.truemfg.com for school milk profit calculator.

Remote cabinets available 14% off list (condensing units supplied by others). Consult factory technical service dept. for BTU information.