

TRUE FOOD SERVICE EQUIPMENT, INC.

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546 Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com

Project Nam	AIA#	
Location:		
Item #:	Qty:	SIS #
Model #:		

Model:

TBB-24-60FR

Underbar Refrigeration:

Solid Swing Door 24" Food Rated Back Bar Cooler



TBB-24-60FR

- ▶ True's refrigerated back bar coolers are designed with enduring quality and value. Our commitment to using the highest quality materials and oversized refrigeration assures colder product temperatures and years of trouble free service.
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (.5°C to 3.3°C).
- ▶ Exterior heavy duty, wear resistant laminated black vinyl front and sides. Matching black aluminum back. All stainless steel counter top.
- Interior stainless steel.
- NSF-7 approved for open food product.
- Positive seal doors.
- ▶ Entire cabinet structure and solid doors are foamed-in-place using Ecomate. A high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).



ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the nearest %" (millimeters rounded up to next whole number).

		Capac 12 oz.	ity			et Dime (inches) (mm)	ensions)				NEMA	Cord Length (total ft.)	Crated Weight (lbs.)
Model	Doors	Cans		Shelves	L	D†	Н	НР	Voltage	Amps	Config.		(kg)
TBB-24-60FR	2	72 6-pks	3	4	61%	241/2	35%	1/6	115/60/1	4.7	5-15P	7	N/A
					1553	623	905	N/A		N/A		2.13	N/A

† Depth does not include 1" (26 mm) for rear bumpers.

MADE IN SECURITY CULTURE INSE	APPROVALS:	AVAILABLE AT:		
3/15 Printed in U.S.A.				

TBB-24-60FR

Underbar Refrigeration:

Solid Swing Door 24" Food Rated Back Bar Cooler



STANDARD FEATURES

DESIGN

 True's refrigerated back bar coolers are designed with enduring quality and value. Our commitment to using the highest quality materials and oversized refrigeration assures colder product temperatures and years of trouble free service.

REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system using environmentally friendly (CFC free) 134A refrigerant.
- Extra large evaporator coil balanced with higher horsepower compressor and large condenser; maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C).
- Sealed, cast iron, self-lubricating evaporator fan motor(s) and larger fan blades give True back bar coolers a more efficient low velocity, high volume airflow design. This unique design ensures faster temperature pull down of warm product, colder holding temperatures and faster recovery in high use situations.
- Condensing unit accessed from behind front grill, slides out for easy cleaning and maintenance.

CABINET CONSTRUCTION

- Exterior heavy duty, wear resistant laminated black vinyl front and sides. Matching black aluminum back. All stainless steel counter top.
- Interior stainless steel.
- Insulation entire cabinet structure and solid doors are foamed-in-place using Ecomate. A high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Welded, heavy duty steel frame rail, black powder coated for corrosion protection.

DOORS

- Wear-resistant laminated black vinyl exterior with heavy gauge galvanized steel door liner.
- Each door fitted with 12" (305 mm) long recessed handle that is foamed-in-place with a sheet metal interlock to ensure permanent attachment.
- · Positive seal doors.
- Magnetic door gaskets of one piece construction, removable without tools for ease of cleaning.
- · Door locks standard.

SHELVING

Four (4) adjustable, heavy duty, black PVC coated wire shelves 23 ¾ "L x 18"D (604 mm x 458 mm). Four (4) chrome plated shelf clips included per shelf.

Aluminum shelf support pilasters.
Shelves are adjustable on ½" (13 mm) increments.

LIGHTING

• Fluorescent interior lighting. Safety shielded.

MODEL FEATURES

- Evaporator is epoxy coated to eliminate the potential of corrosion.
- Designed to accommodate a variety of beer kegs.
- NSF-7 compliant for open food product.

ELECTRICAL

 Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.



OPTIONAL FEATURES/ACCESSORIES

Upcharge and lead times may apply.

 \square 6" (153 mm) standard legs.


☐ 6" (153 mm) seismic/flanged legs.


 \square 2 ½" (64 mm) diameter castors.

□ 4" (102 mm) diameter castors.

☐ Additional shelves.

PLAN VIEW





WARRANTY*

Three year warranty on all parts and labor and an additional 2 year warranty on compressor. (U.S.A. only)

*RESIDENTIAL APPLICATIONS: TRUE assumes no liability for parts or labor coverage for component failure or other damages resulting from installation in non-commercial or residential applications.

METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

KCL	Model	Elevation	Right	Plan	3D	Back
	TBB-24-60FR	TFJX56E	TFJX27S	TFJX35P	TFJX563	

TRUE FOOD SERVICE EQUIPMENT